

# BT EXTRA

Maximise your  
baling efficiency



## SUSTAINABLE INNOVATION

- BT Extra is an advanced, extended-length twine engineered for standard large square baling. It's innovative tape construction ensures a uniform, cylindrical twine that delivers superior knot holding performance.
- Designed specifically to promote a smoother, less abrasive passage through the baler, enhancing operational efficiency and longevity.



## PRODUCT SPECIFICATIONS

ITEM CODE	DESCRIPTION	UOM	LENGTH/PACK	COLOUR	PLT QTY	BALES PER PLT 6-STRING*
66212550	BT Extra	Pk 2	2,550m	Blue	24	1536

\* Approx bale qty based on 8x3x4 bale (2400m x 900m x 1200m)

## FEATURES

1. Extra length spools
2. Smooth run through the baler
3. Australian optimised design with 12 months UV Protection
4. High visibility colour (blue)

## BENEFITS

1. Increases the number of bales produced per spool, reducing downtime and enhancing productivity
2. Minimises wear and tear on knotter equipment, extending the lifespan of your machinery and lowering maintenance costs
3. Specifically crafted to endure Australian conditions, with a 12-month guarantee against degradation.
4. Enhances visibility, making it easier to manage and monitor baling operations, improving overall efficiency and safety.

## APPLICATION TIPS

### APPLICATION TIPS

#### PRE-BALING

The use of a 'rotary' rake in general, makes the best windrows to allow for easy, even nice square bales for owner and operator. Ensuring the hay is cured is critical. The use of hay inoculants or pH neutralised preservatives such as Hay Shield or Hay Mate is recommended for pushing the baling window wider and/or earlier baling to improve leaf retention, colour and feed test.

## BALING

### IT'S IMPORTANT TO:

1. Check the twine tension.
2. Check bill hook opening.
3. Check the twine disk adjustment to minimise mis-ties.
4. Check the tension on the top and bottom twine holding gears.
5. Check the condition of the needle rollers.
6. The operator must set the correct moisture content, bale load and density. If settings are too high or low, this can affect the load on the twine during the tying cycle.
7. Check the knife on the knotter arm is sharp.
8. Check the timing of the knife arm to bill hook. This is critical.
9. Check all wear and tear within the knotting system. Replace liberally – particularly in the new high performance balers.

