

# BIG BLUE

The great  
'all-rounder'

## SUSTAINABLE INNOVATION

- Big Blue round bale twine is one of Agri Novatex signature twines and a long-time favourite for general purpose round baling.
- Developed for Australia's tough baling conditions, Big Blue's combination of strength and longer running length make it the ideal general purpose twine. Suitable for all crop types including pasture, cereal, straw and silage. Also applicable for use across the horticulture industry for vine twines, tomatoes, bananas and citrus.



## PRODUCT SPECIFICATIONS

ITEM CODE	DESCRIPTION	UOM	LENGTH/PACK	COLOUR	PLT QTY
60299925	Big Blue Round	Pk 2	12000m	Blue	40

\* Approx bale qty based on 8x3x4 bale (2400m x 900m x 1200m)

## FEATURES

1. Signature strength
2. Long running length
3. Versatile application
4. Compability with modern balers

## BENEFITS

1. Superior strength ensures reliable performance, even in Australias tough baling conditions. This durability minimises twine breakages, reducing downtime and increasing productivity
2. Extended spool length allows for more bales per spool, reducing the need for frequent spool changes. Efficiency saves time and labour.
3. Designed to work seamlessly with all modern conventional round balers. Compability provides peace of mind.

## APPLICATION TIPS

### APPLICATION TIPS

#### PRE-BALING

The use of a 'rotary' rake in general, makes the best windrows to allow for easy, even nice square bales for owner and operator. Ensuring the hay is cured is critical. The use of hay inoculants or pH neutralised preservatives such as Hay Shield or Hay Mate is recommended for pushing the baling window wider and/or earlier baling to improve leaf retention, colour and feed test.

## BALING

### IT'S IMPORTANT TO:

1. Check the twine tension.
2. Check bill hook opening.
3. Check the twine disk adjustment to minimise mis-ties.
4. Check the tension on the top and bottom twine holding gears.
5. Check the condition of the needle rollers.
6. The operator must set the correct moisture content, bale load and density. If settings are too high or low, this can affect the load on the twine during the tying cycle.
7. Check the knife on the knotter arm is sharp.
8. Check the timing of the knife arm to bill hook. This is critical.
9. Check all wear and tear within the knotting system. Replace liberally – particularly in the new high performance balers.

